

# AccuGrind 90

## Cutting and Grinding Lubricant



### Description:

**AccuGrind 90** is a premium quality petroleum- based cutting and grinding lubricant.

**AccuGrind 90** is chlorine and active-sulfur free but is fortified with an extreme pressure additive of the latest generation.

### Key Properties:

- ✓ Provides excellent metal removal
- ✓ Superior part finish
- ✓ Prolonged tool life
- ✓ Enhanced resistance to high temperatures and pressures
- ✓ High chemical stability

### Typical Specifications:

TEST	RESULT
Appearance	Clear Amber
Color, ASTM D 1500	1.5
Viscosity @ 40 °C, cSt	18.20
Flash Point, COC, °F	355
Active Sulfur	None
Chlorine	None
Inactive-Sulfur, %	1.2
Lubricity Agent, %	6.0
Specific Gravity @ 60°F	0.868
Lbs per Gallon	7.24

### Applications:

- Cutting and Grinding

### Material Compatibility:

**AccuGrind 90** can be used on ferrous and non-ferrous metals.

### Safe Handling and Storage Instructions:

Before handling and using, the Safety Data Sheet (SDS) should be read and understood by all personnel in contact with this product. General indoor storage at room temperature is recommended. **DO NOT FREEZE**

### Disposal:

Any disposal of this product should be in compliance with all federal, state and local regulations. Please refer to the Safety Data Sheet (SDS) for instructions regarding proper disposal of this product.

### Precautions:

#### **KEEP OUT OF THE REACH OF CHILDREN.**

Please refer to the label and Safety Data Sheet for all warnings, recommendations for safety equipment, and other regulatory information. Copies of the Safety Data Sheet (SDS) can be ordered by calling 800-438-2647.

This information is presented in good faith, but no warranty, expressed or implied is given. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. This is an uncontrolled copy and changes can be made to this document without notice.